



# Bull Nose Grinder

## HG60

### SPECIFICATIONS



ITEM	U.S.A.	METRIC
CAPACITY	2.5 in. Diameter x 2.75 in.	
PERFORMANCE	4500 rpm	
FLOW RANGE	5 - 10 gpm	19 - 38 lpm
PRESSURE	2000 psi	140 bar
PORTS	-8 SAE O-Ring	
WEIGHT	11.3 lbs	5.13 kg
LENGTH	23 in.	58.4 mm
WIDTH	3.3 in.	8.4 cm
HEIGHT	4 in.	10.2 cm
CONNECTION	HTMA Flush Face Couplers	
HOSE WHIPS	Yes	
MOTOR	Integral	
ARBOR	5/8 in. -11	

### Features and Benefits

The Stanley HG60 Bull Nose Grinder is ideal for smoothing weld seams, de-burring drilled holes, cleaning castings, or any application where removal of unwanted metal is needed.

The HG60's hydraulic motor is specifically designed to optimize power and rpm for grinding applications. The HG60 won't bog down on those tough grinding jobs. And, its compact and lightweight design helps reduce operator fatigue.

A built-in flow control valve prevents the chance of excessive spindle speed and also protects the motor, resulting in increased tool life. An interlocking trigger assembly helps prevent accidental engagement of the tool, providing increased operator safety.



## ORDERING INFORMATION

MODEL	PART NO.	DESCRIPTION
HG60	HG60130B	2-1/2 in. Diameter

## WARRANTY

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

All Stanley Hydraulic Tools, parts, accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your applications, please consult Stanley Hydraulic Tools.

**STANLEY**<sup>®</sup>

Stanley Hydraulic Tools  
3810 S.E. Naef Road  
Milwaukie, Oregon 97267  
Tel 503 • 659 • 5660  
Fax 503 • 652 • 1780